

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** Aerosol Kupfer-Gold-Effekt
- **(Article number) product ID.:** REZ53
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the mixture:** painting
- **Uses advised against** No further relevant information available.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Peter Kwasny GmbH  
Heilbronner Str. 96  
D-74831 Gundelsheim
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Tel.: +49 6269 95 20
- **national:**  
National Poisons Information Service, Birmingham  
Tel.: 844 892 0111
- **K-Nr.** 0001

Tel.: 0049-(0)6269-95-20  
E-mail: labor@kwasny.de

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Aerosol 1      H222-H229      *Extremely flammable aerosol. Pressurised container: May burst if heated.*



STOT RE 2      H373      *May cause damage to the hearing organs through prolonged or repeated exposure.*



Aquatic Chronic 2 H411      *Toxic to aquatic life with long lasting effects.*



Skin Irrit. 2      H315      *Causes skin irritation.*

Eye Irrit. 2      H319      *Causes serious eye irritation.*

STOT SE 3      H335      *May cause respiratory irritation.*

Asp. Tox. 1      H304      *May be fatal if swallowed and enters airways.*

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

Trade name: Aerosol Kupfer-Gold-Effekt

(Contd. of page 1)

## · 2.2 Label elements

## · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

## · Hazard pictograms



GHS02 GHS07 GHS08 GHS09

· Signal word *Danger*

## · Hazard-determining components of labelling:

xylene, mixture of isomers

ethylbenzene

## · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

## · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## · Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH208 Contains methyl methacrylate, n-butyl methacrylate. May produce an allergic reaction.

## · Information concerning particular hazards for human and environment: 1272/2008/EC,II, 3.2

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

GB

(Contd. on page 3)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

Trade name: Aerosol Kupfer-Gold-Effekt

(Contd. of page 2)

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 7440-50-8 EINECS: 231-159-6	copper Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Eye Irrit. 2, H319	2.5-<5%
CAS: 7440-66-6 EINECS: 231-175-3 Reg.nr.: 01-2119467174-37-xxxx	zinc powder -zinc dust (stabilized) Flam. Sol. 1, H228; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-<2.5%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-xxxx	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<1%
CAS: 97-88-1 EINECS: 202-615-1 Reg.nr.: 01-2119486394-28-xxxx	n-butyl methacrylate Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<1%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media -**

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

Trade name: Aerosol Kupfer-Gold-Effekt

(Contd. of page 3)

- **Suitable extinguishing agents:** Cool container with water
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene, mixture of isomers

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm
	Sk; BMGV

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

Trade name: **Aerosol Kupfer-Gold-Effekt**

(Contd. of page 4)

**106-97-8 butane (containing  $\leq 0,1$  % butadiene (203-450-8))**

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

**100-41-4 ethylbenzene**

WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Sk

**80-62-6 methyl methacrylate**

WEL Short-term value: 416 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 208 mg/m<sup>3</sup>, 50 ppm

**· Ingredients with biological limit values:****1330-20-7 xylene, mixture of isomers**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

**· Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

**· Protection of hands:**

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves** Nitrile rubber, NBR**· Penetration time of glove material**

Gloves must be changed after every contamination.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

butyl rubber, 0,7mm

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

Trade name: *Aerosol Kupfer-Gold-Effekt*

(Contd. of page 5)

- **Eye protection:**  
Safety glasses



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

- |                           |                                    |
|---------------------------|------------------------------------|
| · <b>Form:</b>            | Aerosol                            |
| · <b>Colour:</b>          | According to product specification |
| · <b>Odour:</b>           | Characteristic                     |
| · <b>Odour threshold:</b> | Not determined.                    |

- |                    |                 |
|--------------------|-----------------|
| · <b>pH-value:</b> | Not determined. |
|--------------------|-----------------|

##### · Change in condition

- |   |               |
|---|---------------|
| · <b>Melting point/freezing point:</b>            | Undetermined. |
| · <b>Initial boiling point and boiling range:</b> | -44 °C        |

- |                       |                                   |
|-----------------------|-----------------------------------|
| · <b>Flash point:</b> | -70 °C<br>Without propellant gas. |
|-----------------------|-----------------------------------|

- |                                     |                 |
|-------------------------------------|-----------------|
| · <b>Flammability (solid, gas):</b> | Not applicable. |
|-------------------------------------|-----------------|

- |                                |        |
|--------------------------------|--------|
| · <b>Ignition temperature:</b> | 365 °C |
|--------------------------------|--------|

- |                                     |                 |
|-------------------------------------|-----------------|
| · <b>Decomposition temperature:</b> | Not determined. |
|-------------------------------------|-----------------|

- |                                     |                              |
|-------------------------------------|------------------------------|
| · <b>Auto-ignition temperature:</b> | Product is not selfigniting. |
|-------------------------------------|------------------------------|

- |                                |  |
|--------------------------------|--|
| · <b>Explosive properties:</b> | Product is not explosive. However, formation of explosive air/vapour mixtures are possible.<br>Not determined. |
|--------------------------------|--|

##### · Explosion limits:

- |                 |            |
|-----------------|------------|
| · <b>Lower:</b> | 1 Vol %    |
| · <b>Upper:</b> | 10.9 Vol % |

- |                                    |          |
|------------------------------------|----------|
| · <b>Vapour pressure at 20 °C:</b> | 3600 hPa |
|------------------------------------|----------|

- |                            |                         |
|----------------------------|-------------------------|
| · <b>Density at 20 °C:</b> | 1.413 g/cm <sup>3</sup> |
| · <b>Relative density</b>  | Not determined.         |
| · <b>Vapour density</b>    | Not determined.         |
| · <b>Evaporation rate</b>  | Not applicable.         |

- |  |                                   |
|--|-----------------------------------|
| · <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix. |
|--|-----------------------------------|

- |  |                 |
|--|-----------------|
| · <b>Partition coefficient: n-octanol/water:</b> | Not determined. |
|--|-----------------|

##### · Viscosity:

- |                     |                 |
|---------------------|-----------------|
| · <b>Dynamic:</b>   | Not determined. |
| · <b>Kinematic:</b> | Not determined. |

##### · Solvent content:

- |                            |   |
|----------------------------|---|
| · <b>Organic solvents:</b> | 86.2 %<br>With propellant gas. Content given by weight. |
|----------------------------|---|

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

Trade name: Aerosol Kupfer-Gold-Effekt

(Contd. of page 6)

VOC (EU)	86.05 %
Solids content:	13.9 %
· 9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### ATE (Acute Toxicity Estimates)

Oral	LD50	10220 mg/kg
Inhalative	LC50/4 h	111 mg/l

##### 1330-20-7 xylene, mixture of isomers

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	12126 mg/kg (rabbit)
Inhalative	LC50/4 h	27.571 mg/l (rat) 4h

- Primary irritant effect:
- Skin corrosion/irritation  
Causes skin irritation.
- Serious eye damage/irritation  
Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure  
May cause respiratory irritation.
- STOT-repeated exposure  
May cause damage to the hearing organs through prolonged or repeated exposure.
- Aspiration hazard  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

Trade name: Aerosol Kupfer-Gold-Effekt





(Contd. of page 7)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   | UN1950  |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul> | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (copper, zinc powder -zinc dust (stabilized)), MARINE POLLUTANT AEROSOLS, flammable   |
| <ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR</b></li> </ul>  | <div style="display: flex; align-items: center; gap: 10px;">   </div> |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>  | 2 5F Gases.<br>2.1  |
| <ul style="list-style-type: none"> <li>· <b>IMDG</b></li> </ul>   | <div style="display: flex; align-items: center; gap: 10px;">   </div> |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> </ul>  | 2.1   |

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

Trade name: Aerosol Kupfer-Gold-Effekt

(Contd. of page 8)

· **Label** 2.1

· **IATA**



· **Class** 2.1  
· **Label** 2.1

· **14.4 Packing group**  
· **ADR, IMDG, IATA** Void  
not classified

· **14.5 Environmental hazards:**  
· **Marine pollutant:** Yes  
Symbol (fish and tree)  
· **Special marking (ADR):** Symbol (fish and tree)

· **14.6 Special precautions for user** Warning: Gases.  
· **Hazard identification number (Kemler code):** -  
not classified  
· **EMS Number:** F-D,S-U  
· **Segregation groups** Heavy metals and their salts (including their organometallic compounds), powdered metals  
SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre:  
Category A. For AEROSOLS with a capacity above 1 litre:  
Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
· **Stowage Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2.  
For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**  
· **Limited quantities (LQ)** 1L  
· **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity  
· **Transport category** 2  
· **Tunnel restriction code** D

· **IMDG**  
· **Limited quantities (LQ)** 1L  
· **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

GB

(Contd. on page 10)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

Trade name: Aerosol Kupfer-Gold-Effekt

(Contd. of page 9)

#### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
VOC: <840g/l

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
III	2.5-<5
NK	50-100

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.03.2021

Revision: 11.03.2021

**Trade name: Aerosol Kupfer-Gold-Effekt**

(Contd. of page 10)

*Flam. Gas 1A: Flammable gases – Category 1A**Aerosol 1: Aerosols – Category 1**Press. Gas (Comp.): Gases under pressure – Compressed gas**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Flam. Sol. 1: Flammable solids – Category 1**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2***\* Data compared to the previous version altered.**

GB