

Product information | TECHNICAL DATA SHEET

MEGA COLORS. Solid Colors. Glossy paint, high pressure, best opacity and high powered.
600 ml, 15.5 Oz, 440 g.

GENERAL DESCRIPTION

Alkyd gloss enamel, formulated with high quality pigments and with a very fast drying action. It leverages the power of the valve to spray the paint at high speed, obtaining a much wider span and a more fluid coat of paint. For a perfect finish with very good colour retention and weather resistance.

FEATURES

- High pressure.
- Very fast drying.
- Excellent flexibility.
- Easy to apply and repaint.
- Good hardening.
- Does not contain lead nor other heavy metals.
- High covering capability.
- Good resistance to the outdoors.
- Color and brightness durability.
- Good resistance to UV light (see chart).
- Strong resistance to scratching once the film is polymerized.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush and prepare an anti-rust primer if considered necessary.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within fifteen minutes with the same paint.
- Turn the aerosol upside down to clean out the valve after use. If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

High pressure:	Fast female valve
Propellant:	Butane / Propane / Mix
Type de liant:	Modified alkyd
Color:	See Chart
Shine 60° (ASTM D-523 ISO 2813):	60-90
Dry to the touch (ASTM D-1640 ISO 1517):	15'
Completely dry (ASTM D-1640 ISO 1517):	24 h
Thickness of dry layer (ASTM D-823 ISO 2808):	15 micras/capa
Adherence (ASTM D-3359 ISO 2409):	3 B
Theoretical yield (continuous painting):	5,75 m ² to 600 ml
Thinner:	Mix
Product life:	(Well Stored) 10 years
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity 85% R.H.P
Heat resistance of paint:	100°C
Repintado:	After 15'

* All of the adherence tests have been carried out on iron plates.

APPLICATIONS

Owing to the product's characteristics, the recommended use is for retouches and painting on all types of materials, whether for domestic uses, crafts, fine arts, or ultimately for anything which requires the properties found in a high-quality spray paint.

- Graffiti and muralism
- Gardening
- Fine arts
- Signage
- DIY

APPEARANCE



LABEL



CAP SYSTEM



COLORS 15 Colors

RV 1021 Amarillo Claro / Light Yellow EX0161021	RV 216 Violeta Anonymus / Anonymous Violet EX0160216	R 9010 Blanco Divinidad / Divinity White EX0169010
RV 2003 Naranja Pastel / Pastel Orange EX0162003	RV 8 Azul Claro / Light Blue EX0160008	RV 7040 Gris Perla / Pearl Gray EX0167040
RV 3020 Rojo Claro / Light Red EX0163020	RV 30 Azul Eléctrico / Electric Blue EX0160030	R 9011 Negro / Black EX0169011
RV 211 Rosa Amor / Love Pink EX0160211	RV 34 Verde Guacamole / Guacamole Green EX0160034	
RV 4010 Magenta EX0164010	RV 219 Verde Paris / Paris Green EX0160219	
RV 225 Violeta Geisha / Geisha Violet EX0160225	RV 8002 Marrón Tostado / Toasted Brown EX0168002	

☼☼☼ Outside endurance █ █ █ █ Opacity level



PACKAGING

High pressure.
 Heat resistance of packaging: <50°C
 Propellant: GLP – HC C₃-C₄
 Nominal capacity: 600 ml.

Box (6 units)
 200 X 280 X 140 mm.



Due to technical reasons this color chart might not reproduce the real colors. For accurate color reference see the spraycan's Donut. © Montana Colors 2020.