Product information | TECHNICAL DATA SHEET

MEGA PLATA. Metallic silver colour. Glossy paint, high pressure, high covering and high powered. 600 ml, 16.75 Oz, 475 g.

GENERAL DESCRIPTION

Mega Plata in a 600 ml format allows you to paint larger surfaces in less time. Acrylic gloss enamel, formulated with very high quality resins and leafing aluminium. With a very fast drying action, it leverages the power of the valve to expel the paint at high speed, obtaining a much wider span and a more fluid coat of paint. For a perfect finish and optimum exterior resistance.

FEATURES

- Very fast drying.
- High covering capability.
- Good adhesion.
- Does not contain lead
- Light weather resistance.
- Aluminio de tipo leafing.
- It doesn't resist abrasion.

APLICACIONES

Very suitable for painting any type of surface, giving a highly decorative metallic aspect. Very suitable for artworks.

- Graffiti

- Fine arts - DIY

- Plastics - Retouching metallic components

- Decoration

Paint with low exterior resistance and low resistance to abrasion, which leads to a loss of the metallic appearance. Do not apply coats of varnish or other paints due to the leafing aluminium, which migrates to the surface.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute.
 Does not contain mixture balls inside.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush and prepare an anti-rust primer if considered necessary.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within fifteen minutes with the same paint.
- Turn the aerosol upside down to clean out the valve after use, If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

| Binding type: | Acrylic resin |
|---|--------------------------------|
| Color: | Gloss silver |
| Dry to the touch (ASTM D-1640 ISO 1517): | 10' |
| Completely dry (ASTM D-1640 ISO 1517): | 30' |
| Thickness of dry layer (ASTM D-823 ISO 2808): | 25 micras/layer (2 coats) |
| Adherence (ASTM D-3359 ISO 2409): | 3 B |
| Theorical yield (continuous painting): | 9,6 m ² for 600 ml |
| Thinner: | Aromatic mixture |
| Product life: | (Well Stored) 10 Years |
| Condition for application: | Minimum room temperature 8°C |
| | Surface temperature 5°C a 50°C |
| | Max humidity 85% R.H.P |
| Heat resistance of paint: | 150°C |
| Recoating: | After 15' |

^{*} All of the adherence tests have been carried out on iron plates.

APPEARANCE



LABEL CAP SYSTEM









PACKAGING

High pressure. Heat resistance of packaging: <50°C Propellant: GLP - HC C3-C4 Nominal capacity: 600 ml.

Box (6 units) 200 X 280 X 140 mm.



Montana Colors, S.L. P.I. Clot del Tufau - 08295 Sant Vicenç de Castellet BARCELONA T.: +34 938 332 787 - montana@montanacolors.com - www.montanacolors.com