

Product information | TECHNICAL DATA SHEET

ANTI RUST PRIMER

400 ml, 10.7 Oz, 304 g.

GENERAL DESCRIPTION

Anti rust primer formulated with acrylic resins and corrosion inhibitor pigments, makes it ideal for protecting any iron surface.

FEATURES

- Fast drying.
- Good elasticity.
- Easy of application and recoating.
- Good adherence.
- Does not contain lead.
- High covering power.
- Very high resistance to outdoor exposure.
- High anti-corrosion power.

APPLICATIONS

Suitable as primer in spray paint systems. Its anticorrosive power makes it ideal as a primer coat for protecting any iron surface.

- Automotive industry
- Industrial applications
- Metal structures
- DYI
- Maintenance

INSTRUCTIONS FOR USE

- Shake can vigorously for one minute after hearing mixer noise.
- Thoroughly clean, degrease, and dry the object to be painted. On rusty metallic surfaces, remove corrosion using a wire brush.
- Apply thin coats for best results, always thin layers is better than one thick, paintable after ten minutes with the same paint.
- Disconnect the electrical appliance before painting. Use it in well ventilated areas.
- Request safety data sheets.

PHYSICAL PROPERTIES

Brinder type:	Acrylic
Color:	Gray, Red
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	30'
Thickness of dry layer (ASTM D-823 ISO 2808):	15 µ/layer
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical coverage (continuous painting):	2,5 m² for 400 ml 0,70 m² for 150 ml
Thinner:	Butyl Acetate
Product life:	(Well Stored) 5 Years
Recoating:	After 10'
Painted resistance to heat:	160°C
Application conditions:	Ambient temperature 8°C Surface temperature 5-50°C Humidity Max. 85% R.H.P

*Adherence tests were performed on steel.

280421

IMAGE



LABEL



Gris / Gray
EX014PR0115

Rojo / Red
EX014PR0131

CAP SYSTEM



Pocket Cap
Fino - Fine

PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

