## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Speedflow
- · Article number: 367.000, 467.000, 667.000, 767.000, 691.767, 211.021, 211.022
- · Registration number

The ingredients of this ink have been pre-registered according to 1907/2006/EC (REACH)

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Currently no such applications are identified
- · Application of the substance / the mixture alcohol based permanent marking ink
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Feuerstein GmbH MOLOTOW Distribution Willy-Brandt-Straße 9/2 D 77933 Lahr / Schwarzwald Phone +49 (0) 7821 92 229 0 [8:00 - 17:00 (UTC+1)] Fax +49 (0) 7821 92 229 99 www.molotow.com

· 1.4 Emergency telephone number:

Feuerstein GmbH MOLOTOW Distribution Phone +49 (0) 7821 92 229 0 [8:00 - 17:00 (UTC+1)]

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

H225 Highly flammable liquid and vapour. Flam. Liq. 2



GHS08 health hazard

Muta. 2 H341 Suspected of causing genetic defects. H351 Suspected of causing cancer. Carc. 2



GHS05 corrosion

Eve Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

H315 Causes skin irritation. Skin Trrit. 2

H317 May cause an allergic skin reaction. Skin Sens. 1

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

Trade name: MA 2010 black

· Hazard pictograms



· Signal word Danger

#### · Hazard-determining components of labelling:

Phosphoric acid mono-bis-(2-ethylhexyl)-ester

C. I. Solvent Orange 3
C. I. Solvent Violet 8

C. I. Solvent Blue 4 < 0,1% Michler's Ketone

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction. H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H410 Very toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

- $\cdot$  Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

Mixture of the following substances, containing non-hazardous substances and colouring agents.

## Description:

All ingredients of the ink Speedflow are pre-registered according to 1907/2006/EC (REACH). For pre-registration numbers refer to the list attached to his MSDS.

· Dangerous componen	ts:	
CAS: 64-17-5 EINECS: 200-578-6	ethanol      Flam. Liq. 2, H225;    Eye Irrit. 2, H319	50-100%
CAS: 107-98-2	1-Methoxy-2-propanol	2,5-10%
EINECS: 203-539-1 CAS: 12645-31-7	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336 Phosphoric acid mono-bis-(2-ethylhexyl)-ester	2,5-10%
EINECS: 235-741-0	♦ Skin Corr. 1B, H314	, , , , , , , , , , , , , , , , , , ,
CAS: 84281-86-7 EINECS: 282-630-8	C. I. Solvent Violet 8  Eye Dam. 1, H318; () Acute Tox. 4, H302	2,5-10%
CAS: 495-54-5 EINECS: 207-803-7	C. I. Solvent Orange 3  Muta. 2, H341; Carc. 2, H351; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	2,5-10%
CAS: 6786-83-0 EINECS: 229-851-8	C. I. Solvent Blue 4 < 0,1% Michler's Ketone  Skin Sens. 1B, H317; Aquatic Chronic 3, H412	<u>&lt;</u> 1,0%

· Additional information: For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

- $\cdot$  4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

(Contd. of page 2)

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- $\cdot$  7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

 $\cdot$  7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- $\cdot$  Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-Methoxy-2-propanol (2,5-10%)

IOELV Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls

Skin

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

(Contd. on page 4)

(Contd. of page 3)

Avoid contact with the eyes and skin.

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Partition coefficient (n-octanol/water):

SECTION .	9: .	Physi	cal	and	chemi	cal	pro	perti	es
-----------	------	-------	-----	-----	-------	-----	-----	-------	----

9.1 Information on basic physical and che General Information	emical properties
Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour:	Product specific
Odour threshold:	Not determined.
· Important information on protection of h	ealth and
environment, and on safety.	=
	<del>-</del>
pH-value at 20 °C:	5
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	78 °C
Flash point:	13 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	287 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1,7 Vol %
Upper:	15,0 Vol %
Vapour pressure at 20 °C:	59 hPa
Density:	Not determined.
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

Fully miscible.

Not determined.

(Contd. on page 5)

Printing date 06.05.2015 Revision: 06.05.2015 Version number 31

	(Contd. of page 4
· Viscosity:	
Dynamic at 20 °C:	4,2 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	76,2 %
Solids content:	14,7 %
· 9.2 Other information	No further relevant information available.

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- $\cdot$  10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitisation: Sensitisation possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Muta. 2, Carc. 2

# SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

## 6786-83-0 C. I. Solvent Blue 4 < 0,1% Michler's Ketone

EC50 / 48h 0,025 mg/l (Daphnie)

- · 12.2 Persistence and degradability No further relevant information available.
- $\cdot$  12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- Remark: Very toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue				
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS			
08 01 00	wastes from MFSU and removal of paint and varnish			
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances			
	(Contd. on page 6)			

(Contd. of page 5)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	
· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1263
<ul><li>14.2 UN proper shipping name</li><li>ADR</li><li>IMDG</li></ul>	1263 PAINT, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS PAINT (chrysoidine, triarylmethan dye, blue),
· IATA	MARINE POLLUTANT PAINT
· 14.3 Transport hazard class(es)	
· ADR	
· Class	3 (F1) Flammable liquids.
· Label · IMDG	3
· Class · Label · IATA	3 Flammable liquids. 3
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: chrysoidine
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
<ul> <li>14.6 Special precautions for user</li> <li>Danger code (Kemler):</li> <li>EMS Number:</li> </ul>	Warning: Flammable liquids. 33 F-E,S-E
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	<del></del>
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

Remarks 1263 Paint (dye-stuff C.I. Solvent Orange 3), Marine Pollutant · UN "Model Regulation": UN1263, PAINT, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS, 3, II

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

```
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
```

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) Flam. Liq. 2: Flammable liquids, Hazard Category 2
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Muta. 2: Germ cell mutagenicity, Hazard Category 1
Muta. 2: Germ cell mutagenicity, Hazard Category 1

Muta. 2: Germ cell mutagenicity, Hazard Category 2
Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

\* Data compared to the previous version altered.